

Product Category	Model #	Temperature Control	Approximate Product Temp*	Container Volume**	Container Dimensions**	Plug Type	AC Voltage	Nominal Power	Nominal Amperage	Approximate Weight/ Mass	MSRP
Curemax	CM18x18G	Internal Preset	190° F (± 10° F) / 87.7° C (± 5° C)	1.4' x 1.4' / 0.43 m x 0.43 m	18" x 18" x 1"	15 AMP Plug	120v	165W	1.4	2lbs	\$419
Curemax	CM24x24G	Internal Preset	190° F (± 10° F) / 87.7° C (± 5° C)	1.85' x 1.85' / 0.57m x 0.57m	24" x 24" x 1"	15 AMP Plug	120v	275W	2.3	2lbs	\$451
Curemax	CM36x36G	Internal Preset	190° F (± 10° F) / 87.7° C (± 5° C)	2.8' x 2.8' / .85 m x .85 m	36" x 36" x 1"	15 AMP Plug	120v	720W	6	4lbs	\$557
Curemax	CM36x48G	Internal Preset	190° F (± 10° F) / 87.7° C (± 5° C)	2.8' x 3.7' .85 m x 1.1 m	36" x 48" x 1"	15 AMP Plug	120v	800W	6.7	6lbs	\$631

All standard AC products are Certified by ETL to applicable UL and CSA standards (cETLus). Most products are available in 240VAC and Class 1 Division 2 (CID2) hazardous location versions. Contact Powerblanket for more information.

Powerblanket reserves the right to improve products and change specifications without notification
 *Max product temperatures are estimates only, actual temperatures will vary depending on ambient conditions like air temperature, wind, etc.

